

Cover Page for Safety Data Sheet

Thank you for choosing CHEMetrics, Inc. We appreciate your business. In order to best serve your needs for accurate and complete Safety Data, we offer the following information as supplemental to the attached SDS.

SDS No.: R2505

Version No.: 3.4

Product Name: Chlorine CHEMets® & ULR CHEMets® Refills

Part Nos.: R-2505, R-2505V, R-2511

Product Descriptions:

CHEMets Refills: Sealed glass ampoules, 7 mm OD, for visual colorimetric water analysis. Each CHEMet™ ampoule contains approximately 0.25 mL of liquid reagent sealed under vacuum. Refills contain 30 ampoules, test kits contain 1 refill.

ULR CHEMets Refills: Sealed glass ampoules, 250 mm length, for visual colorimetric water analysis. Each ULR CHEMet™ ampoule contains approximately 1 mL of liquid reagent sealed under vacuum. Refills contain 30 ampoules, test kits contain 1 refill.

Addendum to Section 14 Transport Information:

Shipping container markings and labels for this product, as received, may vary from the contents of section 14 of the SDS for one or both of the following reasons:

- CHEMetrics has packaged this product as Dangerous Goods in Excepted Quantities according to IATA, US DOT, and IMDG regulations.
- CHEMetrics has packaged this product as part of a test kit or reagent set composed of various chemical reagents and elected to ship as UN 3316 Chemical Kit, Hazard Class 9, Packing Group II or III.

In case of reshipment, it is the responsibility of the shipper to determine appropriate labels and markings in accordance with applicable transportation regulations.

Additional Information:

- “Print Date” = Revision Date (expressed as DD/MM/YYYY)
- Test kits and reagents sets may contain additional chemical reagents. See separate SDS(s).

CHEMets®, *VACUettes®*, *Vacu-vials®*, and *Titrets®* are registered trademarks of CHEMetrics Inc.



Chlorine CHEMets & ULR CHEMets Refills

CHEMetrics, Inc.

Chemwatch: 9-91794

SDS No: R2505

Version No: 3.4

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 18/11/2014

Print (Revision) Date: 07/06/2018

S.GHS.USA.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Chlorine CHEMets & ULR CHEMets Refills
Synonyms	Part Nos.: R-2505, R-2505V, R-2511
Proper shipping name	Not Applicable
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Component of water analysis test kits K-2505, K-2505V, K-2511
--------------------------	---

Details of the manufacturer/importer

Registered company name	CHEMetrics, Inc.
Address	4295 Catlett Road, Midland, VA. 22728 United States
Telephone	1-540-788-9026
Fax	1-540-788-4856
Website	www.chemetrics.com
Email	technical@chemetrics.com

Emergency telephone number

Association / Organisation	ChemTel Inc.
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	+01-813-248-0585

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification	Acute Toxicity (Oral) Category 4, Carcinogen Category 1B, STOT - SE Category 2
--------------------	--

Label elements

GHS label elements	
--------------------	--

SIGNAL WORD **DANGER**

Hazard statement (s)

H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H350	May cause cancer
H371	May cause damage to organs

Precautionary statement(s) Prevention

P101	If medical advice is needed, have product container or label at hand.
------	---

Continued...

Chlorine CHEMets & ULR CHEMets Refills

P102	Keep out of reach of children.
P103	Read label before use.
P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P270	Do not eat, drink or smoke when using this product.

Precautionary statement(s) Response

P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor/physician/first aider
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P330	Rinse mouth.

Precautionary statement(s) Storage

P405	Store locked up.
------	------------------

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7732-18-5	>90	water
67-56-1	3	methanol
7778-77-0	2-4	potassium phosphate, monobasic
6381-92-6	<1	EDTA disodium salt dihydrate
7664-93-9	<1	sulfuric acid
Not Available	<0.1	Proprietary ingredients
50-00-0	0.1-0.2	formaldehyde

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation. <p>For thermal burns:</p> <ul style="list-style-type: none"> ▶ Decontaminate area around burn. ▶ Consider the use of cold packs and topical antibiotics. <p>For first-degree burns (affecting top layer of skin)</p> <ul style="list-style-type: none"> ▶ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides. ▶ Use compresses if running water is not available. ▶ Cover with sterile non-adhesive bandage or clean cloth. ▶ Do NOT apply butter or ointments; this may cause infection. ▶ Give over-the counter pain relievers if pain increases or swelling, redness, fever occur. <p>For second-degree burns (affecting top two layers of skin)</p> <ul style="list-style-type: none"> ▶ Cool the burn by immerse in cold running water for 10-15 minutes. ▶ Use compresses if running water is not available. ▶ Do NOT apply ice as this may lower body temperature and cause further damage. ▶ Do NOT break blisters or apply butter or ointments; this may cause infection. ▶ Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape. <p>To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort):</p> <ul style="list-style-type: none"> ▶ Lay the person flat. ▶ Elevate feet about 12 inches. ▶ Elevate burn area above heart level, if possible. ▶ Cover the person with coat or blanket. ▶ Seek medical assistance. <p>For third-degree burns</p> <p>Seek immediate medical or emergency assistance.</p> <p>In the mean time:</p> <ul style="list-style-type: none"> ▶ Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound. ▶ Separate burned toes and fingers with dry, sterile dressings. ▶ Do not soak burn in water or apply ointments or butter; this may cause infection. ▶ To prevent shock see above.

Continued...

Chlorine CHEMets & ULR CHEMets Refills

	<ul style="list-style-type: none"> ▶ For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway. ▶ Have a person with a facial burn sit up. ▶ Check pulse and breathing to monitor for shock until emergency help arrives.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.
Ingestion	<ul style="list-style-type: none"> ▶ IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. ▶ For advice, contact a Poisons Information Centre or a doctor. ▶ Urgent hospital treatment is likely to be needed. ▶ In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. ▶ If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided. Further action will be the responsibility of the medical specialist. ▶ If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS. <p>Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:</p> <ul style="list-style-type: none"> ▶ INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. <p>NOTE: Wear a protective glove when inducing vomiting by mechanical means.</p>

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute and short term repeated exposures to methanol:

- ▶ Toxicity results from accumulation of formaldehyde/formic acid.
- ▶ Clinical signs are usually limited to CNS, eyes and GI tract. Severe metabolic acidosis may produce dyspnea and profound systemic effects which may become intractable. All symptomatic patients should have arterial pH measured. Evaluate airway, breathing and circulation.
- ▶ Stabilise obtunded patients by giving naloxone, glucose and thiamine.
- ▶ Decontaminate with ipecac or lavage for patients presenting 2 hours post-ingestion. Charcoal does not absorb well; the usefulness of cathartic is not established.
- ▶ Forced diuresis is not effective; haemodialysis is recommended where peak methanol levels exceed 50 mg/dL (this correlates with serum bicarbonate levels below 18 mEq/L).
- ▶ Ethanol, maintained at levels between 100 and 150 mg/dL, inhibits formation of toxic metabolites and may be indicated when peak methanol levels exceed 20 mg/dL. An intravenous solution of ethanol in D5W is optimal.
- ▶ Folate, as leucovorin, may increase the oxidative removal of formic acid. 4-methylpyrazole may be an effective adjunct in the treatment. 8-Phenytoin may be preferable to diazepam for controlling seizure.

[Ellenhorn Barceloux: Medical Toxicology]

BIOLOGICAL EXPOSURE INDEX - BEI

Determinant	Index	Sampling Time	Comment
1. Methanol in urine	15 mg/l	End of shift	B, NS
2. Formic acid in urine	80 mg/gm creatinine	Before the shift at end of workweek	B, NS

B: Background levels occur in specimens collected from subjects **NOT** exposed.

NS: Non-specific determinant - observed following exposure to other materials.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

	<ul style="list-style-type: none"> ▶ There is no restriction on the type of extinguisher which may be used. ▶ Use extinguishing media suitable for surrounding area.
--	--

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
----------------------	-------------

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Use fire fighting procedures suitable for surrounding area. ▶ DO NOT approach containers suspected to be hot.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. ▶ Not considered a significant fire risk, however containers may burn. <p>May emit poisonous fumes.</p>

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	<ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment.
--------------	--

Continued...

Chlorine CHEMets & ULR CHEMets Refills

	<ul style="list-style-type: none"> ▶ Contain and absorb spill with sand, earth, inert material or vermiculite. ▶ Wipe up.
Major Spills	<p>Moderate hazard.</p> <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water course.
	Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. <p>Wear impact- and splash-resistant eyewear. Break the ampoule tip only when it is completely immersed in sample. Breaking the tip in air may cause the glass ampoule to shatter.</p>
Other information	For optimum analytical performance, store in the dark and at room temperature.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Polyethylene or polypropylene container. ▶ Packing as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	<p>Formaldehyde:</p> <ul style="list-style-type: none"> ▶ is a strong reducing agent ▶ may polymerise in air unless properly inhibited (usually with methanol up to 15%) and stored at controlled temperatures ▶ will polymerize with active organic material such as phenol ▶ reacts violently with strong oxidisers, hydrogen peroxide, potassium permanganate, acrylonitrile, caustics (sodium hydroxide, yielding formic acid and flammable hydrogen), magnesium carbonate, nitromethane, nitrogen oxides (especially at elevated temperatures), peroxyformic acid ▶ is incompatible with strong acids (hydrochloric acid forms carcinogenic bis(chloromethyl)ether*), amines, ammonia, aniline, bisulfides, gelatin, iodine, magnesite, phenol, some monomers, tannins, salts of copper, iron, silver. ▶ acid catalysis can produce impurities: methylal, methyl formate <p>Aqueous solutions of formaldehyde:</p> <ul style="list-style-type: none"> ▶ slowly oxidise in air to produce formic acid ▶ attack carbon steel <p>Concentrated solutions containing formaldehyde are:</p> <ul style="list-style-type: none"> ▶ unstable, both oxidising slowly to form formic acid and polymerising; in dilute aqueous solutions formaldehyde appears as monomeric hydrate (methylene glycol) - the more concentrated the solution the more polyoxymethylene glycol occurs as oligomers and polymers (methanol and amine-containing compounds inhibit polymer formation) ▶ readily subject to polymerisation, at room temperature, in the presence of air and moisture, to form paraformaldehyde (8-100 units of formaldehyde), a solid mixture of linear polyoxymethylene glycols containing 90-99% formaldehyde; a cyclic trimer, trioxane (CH₂O₃), may also form <p>Flammable and/or toxic gases are generated by the combination of aldehydes with azo, diazo compounds, dithiocarbamates, nitrides, and strong reducing agents</p> <p>*The empirical equation may be used to determine the concentration of bis(chloromethyl)ether (BCME) formed by reaction with HCl: $\log(\text{BCME})_{\text{ppb}} = -2.25 + 0.67 \cdot \log(\text{HCHO})_{\text{ppm}} + 0.77 \cdot \log(\text{HCl})_{\text{ppm}}$ Assume values for formaldehyde, in air, of 1 ppm and for HCl of 5 ppm, resulting BCME concentration, in air, would be 0.02 ppb. None known</p>

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	methanol	Methyl alcohol	260 mg/m ³ / 200 ppm	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	methanol	Methanol	200 ppm	250 ppm	Not Available	TLV® Basis: Headache; eye dam; dizziness; nausea; BEI
US NIOSH Recommended Exposure Limits (RELs)	methanol	Carbinol, Columbian spirits, Methanol, Pyroigneous spirit, Wood alcohol, Wood naphtha, Wood spirit	260 mg/m ³ / 200 ppm	325 mg/m ³ / 250 ppm	Not Available	[skin]
US OSHA Permissible Exposure Levels (PELs) - Table Z1	sulfuric acid	Sulfuric acid	1 mg/m ³	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	sulfuric acid	Sulfuric acid	0.2 mg/m ³	Not Available	Not Available	TLV® Basis: Pulm func

Continued...

Chlorine CHEMets & ULR CHEMets Refills


US NIOSH Recommended Exposure Limits (RELs)	sulfuric acid	Battery acid, Hydrogen sulfate, Oil of vitriol, Sulfuric acid (aqueous)	1 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	formaldehyde	Formaldehyde	0.75 ppm	2 ppm	Not Available	see 1910.1048
US OSHA Permissible Exposure Levels (PELs) - Table Z2	formaldehyde	Formaldehyde	0.75 ppm	2 ppm	Not Available	see 1910.1048
US ACGIH Threshold Limit Values (TLV)	formaldehyde	≠ Formaldehyde	Not Available	Not Available	0.3 ppm	TLV® Basis: URT & eye irr
US NIOSH Recommended Exposure Limits (RELs)	formaldehyde	Methanal, Methyl aldehyde, Methylene oxide / Formaldehyde solution [Note: Formalin is an aqueous solution that is 37% formaldehyde by weight; inhibited solutions usually contain 6-12% methyl alcohol. Also see specific listings for Formaldehyde and Methyl alcohol.]	0.016 ppm	Not Available	0.1 ppm	Ca See Appendix A

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
methanol	Methyl alcohol; (Methanol)	Not Available	Not Available	Not Available
potassium phosphate, monobasic	Potassium phosphate, monobasic	29 mg/m3	320 mg/m3	1900 mg/m3
EDTA disodium salt dihydrate	Ethylenediaminetetraacetic acid, disodium salt	11 mg/m3	120 mg/m3	400 mg/m3
EDTA disodium salt dihydrate	Ethylenediaminetetraacetic acid, disodium salt, dihydrate	30 mg/m3	330 mg/m3	2000 mg/m3
sulfuric acid	Sulfuric acid	Not Available	Not Available	Not Available
formaldehyde	Formaldehyde	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
water	Not Available	Not Available
methanol	25,000 ppm	6,000 ppm
potassium phosphate, monobasic	Not Available	Not Available
EDTA disodium salt dihydrate	Not Available	Not Available
sulfuric acid	80 mg/m3	15 mg/m3
Proprietary ingredients	Not Available	Not Available
formaldehyde	30 ppm	20 ppm

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly.</p>
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Suitability and durability of glove type is dependent on usage.</p>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ P.V.C. apron. ▶ Barrier cream. ▶ Skin cleansing cream.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Respiratory protection

Type BEAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001,

Continued...

Chlorine CHEMets & ULR CHEMets Refills

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Chlorine CHEMets & ULR CHEMets Refills, Ozone CHEMets Refill

Material	CPI
NEOPRENE	B
BUTYL	C
BUTYL/NEOPRENE	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
PE	C
PE/EVAL/PE	C
PVA	C
PVC	C
PVDC/PE/PVDC	C
SARANEX-23	C
SARANEX-23 2-PLY	C
TEFLON	C
VITON	C
VITON/NEOPRENE	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	BEAX-AUS P2	-	BEAX-PAPR-AUS / Class 1 P2
up to 50 x ES	-	BEAX-AUS / Class 1 P2	-
up to 100 x ES	-	BEAX-2 P2	BEAX-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Colorless		
Physical state	Liquid	Relative density (Water = 1)	1
Odour	Odourless	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	4	Decomposition temperature	Not Available
Melting point / freezing point (°C)	0	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	95	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.

Chlorine CHEMets & ULR CHEMets Refills

Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of vapours, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Minor but regular methanol exposures may effect the central nervous system, optic nerves and retinae. Symptoms may be delayed, with headache, fatigue, nausea, blurring of vision and double vision.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Skin Contact	Skin contact with the material may be harmful; systemic effects may result following absorption. The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. Liver and/or kidney injury may also result. When administered by inhalation, formaldehyde induced squamous cell carcinomas of the nasal cavity in rats of both sexes.

Chlorine CHEMets & ULR CHEMets Refills	TOXICITY	IRRITATION
Chlorine CHEMets & ULR CHEMets Refills	TOXICITY	IRRITATION

Chlorine CHEMets & ULR CHEMets Refills	No significant acute toxicological data identified in literature search. The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.
WATER	No significant acute toxicological data identified in literature search.
METHANOL	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
POTASSIUM PHOSPHATE, MONOBASIC	No data of toxicological significance identified in literature search.
SULFURIC ACID	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Occupational exposures to strong inorganic acid mists of sulfuric acid:
EDTA DISODIUM SALT DIHYDRATE, FORMALDEHYDE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important.

Acute Toxicity	✓	Carcinogenicity	✓
Skin Irritation/Corrosion	⊘	Reproductivity	⊘
Serious Eye Damage/Irritation	⊘	STOT - Single Exposure	✓

Chlorine CHEMets & ULR CHEMets Refills

Respiratory or Skin sensitisation	☐	STOT - Repeated Exposure	☐
Mutagenicity	☐	Aspiration Hazard	☐

Legend: ✔ – Data required to make classification available
✘ – Data available but does not fill the criteria for classification
☐ – Data Not Available to make classification

CMR STATUS

CARCINOGEN	sulfuric acid	US Environmental Defense Scorecard Recognized Carcinogens	P65
	formaldehyde	US Environmental Defense Scorecard Recognized Carcinogens US Air Toxics Hot Spots TSD for Describing Available Cancer Potency Factors US NIOSH Recommended Exposure Limits (RELs) - Carcinogens	P65 2A Ca See Appendix A
EYE	formaldehyde	US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs) - Eye	Toxic Air Contaminant: The Air Resources Board has identified this substance as a Toxic Air Contaminant. FORMALDEHYDE X
RESPIRATORY	sulfuric acid	US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs) - Respiratory US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs) - Respiratory	X
	formaldehyde	US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs) - Respiratory	X
SKIN	methanol	US - Hawaii Air Contaminant Limits - Skin Designation US - Alaska Limits for Air Contaminants - Skin Designation US NIOSH Recommended Exposure Limits (RELs) - Skin US - Washington Permissible exposure limits of air contaminants - Skin US - Michigan Exposure Limits for Air Contaminants - Skin US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants - Skin US ACGIH Threshold Limit Values (TLV) - Skin US - California Permissible Exposure Limits for Chemical Contaminants - Skin US - North Carolina Permissible Exposure Limits (PELs) for Air Contaminants - Skin Designation [NLV] US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants - Skin US - Minnesota Permissible Exposure Limits (PELs) - Skin	X [skin] Yes S
	formaldehyde	US - Hawaii Air Contaminant Limits - Skin Designation US - Alaska Limits for Air Contaminants - Skin Designation US NIOSH Recommended Exposure Limits (RELs) - Skin US - Washington Permissible exposure limits of air contaminants - Skin US - Michigan Exposure Limits for Air Contaminants - Skin US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants - Skin US ACGIH Threshold Limit Values (TLV) - Skin US - California Permissible Exposure Limits for Chemical Contaminants - Skin US - North Carolina Permissible Exposure Limits (PELs) for Air Contaminants - Skin Designation [NLV] US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants - Skin US - Minnesota Permissible Exposure Limits (PELs) - Skin	X [skin] Yes S

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

For Formaldehyde:

Environmental Fate: Formaldehyde is common in the environment as a contaminant of smoke and as photochemical smog. Concentrated solutions containing formaldehyde are unstable and oxidize slowly. In the presence of air and moisture, polymerization takes place readily in concentrated solutions at room temperature to form paraformaldehyde.

Atmospheric Fate: In the atmosphere, formaldehyde both photolysis and reacts with reactive free radicals (primarily hydroxyl radicals). Reaction with nitrate radicals, insignificant during the day, may be an important removal process at night.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW
methanol	LOW	LOW
EDTA disodium salt dihydrate	LOW	LOW
formaldehyde	LOW (Half-life = 14 days)	LOW (Half-life = 2.97 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)
methanol	LOW (BCF = 10)
EDTA disodium salt dihydrate	LOW (LogKOW = -3.8573)
formaldehyde	LOW (LogKOW = 0.35)

Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)
methanol	HIGH (KOC = 1)
EDTA disodium salt dihydrate	LOW (KOC = 1046)
formaldehyde	HIGH (KOC = 1)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Continued...

Chlorine CHEMets & ULR CHEMets Refills

Product / Packaging disposal	Dispose of according to federal, state, and local regulations.
------------------------------	--

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
------------------	----

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	methanol	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	sulfuric acid	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	formaldehyde	Y

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

water(7732-18-5) is found on the following regulatory lists	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
methanol(67-56-1) is found on the following regulatory lists	"US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Idaho - Limits for Air Contaminants", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US - Hawaii Air Contaminant Limits", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Proposition 65 - Reproductive Toxicity", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - California - Proposition 65 - Priority List for the Development of MADLs for Chemicals Causing Reproductive Toxicity", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Michigan Exposure Limits for Air Contaminants", "US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values", "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US NIOSH Recommended Exposure Limits (RELs)", "US - Alaska Limits for Air Contaminants", "US - Washington Permissible exposure limits of air contaminants", "US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity", "US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants", "US - Minnesota Permissible Exposure Limits (PELs)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US ACGIH Threshold Limit Values (TLV)", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US OSHA Permissible Exposure Levels (PELs) - Table Z1"
potassium phosphate, monobasic(7778-77-0) is found on the following regulatory lists	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
EDTA disodium salt dihydrate(6381-92-6) is found on the following regulatory lists	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
sulfuric acid(7664-93-9) is found on the following regulatory lists	"US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Idaho - Limits for Air Contaminants", "US - Hawaii Air Contaminant Limits", "US - California Permissible Exposure Limits for Chemical Contaminants", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Michigan Exposure Limits for Air Contaminants", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values", "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US NIOSH Recommended Exposure Limits (RELs)", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "US - Alaska Limits for Air Contaminants", "US - Washington Permissible exposure limits of air contaminants", "US - Minnesota Permissible Exposure Limits (PELs)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US ACGIH Threshold Limit Values (TLV)", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Carcinogens", "US OSHA Permissible Exposure Levels (PELs) - Table Z1"
Proprietary ingredients() is found on the following regulatory lists	"Not Applicable"
formaldehyde(50-00-0) is found on the following regulatory lists	"US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)", "US - Idaho - Limits for Air Contaminants", "US - Hawaii Air Contaminant Limits", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US - California Proposition 65 - Reproductive Toxicity", "US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Michigan Exposure Limits for Air Contaminants", "US EPA Carcinogens Listing", "US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Mutagens", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - California - Proposition 65 - Priority List for the Development of MADLs for Chemicals Causing Reproductive Toxicity", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "US - Oregon Permissible Exposure Limits (Z-2)", "US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values", "US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration, Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift", "US OSHA Carcinogens Listing", "US - California

Continued...

Chlorine CHEMets & ULR CHEMets Refills

OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US NIOSH Recommended Exposure Limits (RELs)", "US - Alaska Limits for Air Contaminants", "US - Washington Permissible exposure limits of air contaminants", "US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants", "US - California Proposition 65 - Carcinogens", "US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity", "US OSHA Permissible Exposure Levels (PELs) - Table Z2", "US - Minnesota Permissible Exposure Limits (PELs)", "US ACGIH Threshold Limit Values (TLV)", "US - Idaho - Acceptable Maximum Peak Concentrations", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Carcinogens", "US OSHA Permissible Exposure Levels (PELs) - Table Z1"

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
Not Available	Not Available
Not Available	Not Available

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.